



Kemio Disinfection

The next generation measurement platform



Get consistent results from all your operators. Kemio minimises user input, to ensure **repeatable and reliable results** each time.

Kemio is **suitable for all users**, ready straight out of the box, with **no training required**. Helping to **improve operational efficiency**, by reducing labour time and minimizing disruption.

Go paperless, **protect your data** and meet your compliance requirements. The integrated data log summarises 10,000 results to provide a traceable, auditable dataset.

Kemio is **personalised to your testing needs**, add your unique test and application information to give meaning to your results.

Kemio delivers the results you need from a method you can trust.

Testing for	Range	Temperature
Peracetic acid (PAA)	2 - 2000 mg/L	40°F - 90°F
Chlorine (High Range)	0.1 - 25 mg/L free chlorine 1 - 500 mg/L total chlorine	40°F - 80°F 40°F - 90°F
Chlorine	0.02 - 10 mg/L free chlorine 0.05 - 75 mg/L total chlorine	35°F - 95°F 35°F - 95°F
Chlorine Dioxide	0.02 - 50 mg/L	35°F - 100°F
Chlorite	0.02 - 50 mg/L	35°F - 100°F

Technical Specification

Measuring System	Chrono-amperometry
Temperature Range	Ambient range: 32° F - 120° F
Display	High clarity LCD screen
User Interface	Touchscreen
Language Options	English, French, Spanish and Simplified Chinese
Connectivity	USB
Information Input	Barcode scanner, on-screen keyboard, on-screen keypad
Data Storage	10,000 test results with all test information
Size (W x L x H) & Weight	156 mm x 180 mm x 95 mm, 1012 g
Battery	2300 mAh NiMH Rechargeable Battery Pack <i>Only battery packs supplied by Palintest can be used with Kemio</i>
Power Supply	USB power and external charger
Rating	IP67


Why choose Kemio technology?



A clear pass/fail result, no calculations required




Digital data log, ideal for audits



Electronic measurement not affected by light quality



No glassware



Not affected by color



Not affected by turbidity or floating particles



500 Winmoore Way
Modesto, California 95358
United States of America

Phone: (209) 581-9576
Toll Free: (888) 563-2254
Fax: (209) 581-9653



sales@envirotech.com
customerservice@envirotech.com
www.envirotech.com