

## APPLICATIONS

**REFLEX™** is a new generation no-rinse acid sanitizer used in the dairy, food and beverage processing industry for CIP and COP pipeline, silo, tank and equipment cleaning and sanitizing processes. With regular use **REFLEX™** will prevent the formation of milkstone, beerstone and lime scale deposits. Primarily for use on stainless steel and plastic materials. It is safe to store **REFLEX™** in stainless steel tanks. Do not use on aluminum.

## PROPERTIES

**REFLEX™** has a high oxidation potential and is very reactive. It exhibits excellent bactericidal and fungicidal activity against a wide range of microorganisms in cold or warm water. **REFLEX** contains no phosphates. Product is stable for a minimum of 6 months under normal conditions. It ultimately degrades to nitrogen, oxygen, water, and acetic acid (vinegar).

## FEATURES

- No phosphates
- No rinse needed on food/beverage contact surfaces
- Peroxygen chemistry leaves no residues
- Nitric acid becomes nitrate in wastewater
- For land applied discharges, the nitric component reverts to nitrogen
- Reduces CIP process times and reduces water use
- Economical use at 1 fl oz per 6 gal of hard water.

## CHEMICAL COMPOSITION

**REFLEX** is an equilibrium mixture of peracetic acid, hydrogen peroxide, acetic acid, nitric acid, proprietary ingredients, and water.

Peracetic acid (% wt.)	6.0-6.4
H <sub>2</sub> O <sub>2</sub> (% wt.)	22.5-23.7
Nitric Acid Conc.	6-10%
Phosphates (as PO <sub>4</sub> )	None
Density 20°C (68°F), (g/mL)	1.16-1.20
pH (10% solution), 20°C (68 °F)	<1
Flashpoint (°C)	>98°C (207° F)
Freezing Point	<-12°C (10° F)

## PHYSICAL PROPERTIES

## APPEARANCE

Clear, colorless liquid (pungent vinegar-like odor)

## STORAGE

The **REFLEX** container must be **stored in an upright position**. The storage area should be well ventilated and **shaded from sunlight** as well as protected from sources of radiant heat. Store this product at temperatures where the bulk liquid will not exceed 86°F / 30°C. Contamination of the product, especially metal ions (such as brass, copper or iron) and alkali, must be avoided.

## SHELF LIFE

At least 6 months without notable losses of active oxygen if stored properly.

## PACKAGING

5 gal (40 lb), 53 gal (490 lb), and 300 gal (2780 lb).  
Available in HDPE plastic pails, drums, and totes.

## TRANSPORT(DOT)

Oxidizing liquid, corrosive, n.o.s. (contains hydrogen peroxide and peroxyacetic acid mixture, stabilized), 5.1 (8), UN 3098, PG II

Prod. #37 (V-3/26/2019)

All information and statements contained herein are believed to be accurate at the time of publication, but Enviro Tech Chemical Services, Inc. makes no warranty with respect thereto, including but not limited to any results to be obtained or the infringement of any proprietary rights. Use or application of such information or statements is at user's sole discretion, without any liability on the part of Enviro Tech. Nothing herein shall be construed as a license of or recommendation for use which infringes upon any proprietary rights. Use of this product shall be the sole responsibility of user, and Enviro Tech shall not be liable in any way for said use, other than reimbursement for the actual cost of product.