

TRAY WASH XD

DANGER

**HAZARD STATEMENTS: CAUSES SEVERE SKIN BURNS AND EYE DAMAGE.
MAY BE CORROSIVE TO METALS. MAY BE HARMFUL IF SWALLOWED. CAUSES SERIOUS EYE DAMAGE.**

DIRECTIONS

READ LABEL AND SAFETY DATA SHEET

CLEANING TRAYS: Use a 0.25 - 0.75 % solution (1/4 - 1 ounce per gallon of water) (2 - 8 mL/L). Hot water is recommended for the cleaning solution (130° - 160° F or 54.4° - 71.1° C). Vary the amount, depending on the soil load, water quality and water temperature. Note: Lower water temperatures may be used by increasing the rate of product used.

After cleaning with Tray Wash XD Liquid Tray & Egg Wash, follow-up with an appropriate disinfecting solution. Consult your Tray Wash XD Technical Representative for recommendations.

SHELL EGG CLEANING: Use a 0.25 - 0.75 % solution (1/4 - 1 ounce per gallon of water) (2 - 8 mL/L), depending on water quality and soil on eggs. Recommended temperature of wash water is between 95° - 120° F (35° - 49° C). The wash water should be at least 10° - 15° F (5° - 8° C) warmer than the eggs. If excessive foaming occurs due to egg breakage, an antifoaming agent may be required. After cleaning eggs with Tray Wash XD Liquid Tray & Egg Wash, eggs should be sanitized with an appropriate Tray Wash XD disinfectant. Contact a Tray Wash XD Technical Representative for guidance.

HATCHING EGG CLEANING: Follow directions for shell egg cleaning. Additionally, measure chlorine residuals in recirculating wash tanks and maintain a chlorine reading above 50 ppm using liquid bleach or another suitable product. Drain wash tank every 2 - 3 hours, minimum. If excessive foaming occurs due to egg breakage, an antifoaming agent may be required. After cleaning eggs with Tray Wash XD Liquid Tray & Egg Wash, eggs should be sanitized with an appropriate Tray Wash XD disinfectant. Contact a Tray Wash XD Technical Representative for guidance.

AS A CLEAN-IN-PLACE CLEANER: Flush gross soils from system with a tepid water rinse. Circulate Tray Wash XD Liquid Tray & Egg Wash at 0.5 % solution (1 ounce per 2 gallons water) (4 mL/L) through system at 130° - 160° F (54° - 72° C) for 5 - 10 minutes. Do not let temperature of circulating solution drop below 110° F (43° C). Drain and rinse with potable water or an acidified rinse solution. Sanitize equipment with an approved sanitizer just prior to reuse. Follow recommendations of Federal and local health authorities.

D.O.T. and Hazard Information:

UN1760

Corrosive Liquid, n.o.s., (Potassium Hydroxide), 8, PG II

PRECAUTIONARY STATEMENTS:

Wash hands thoroughly after handling

Wear protective gloves/protective clothing/eye protection/face protection.

Keep only in original container.

Do not eat, drink or smoke when using this product.

Wash contaminated clothing before reuse.

Absorb spillage to prevent material damage.

IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing.

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

IF exposed or you feel unwell: Call a POISON CENTER or doctor/physician.

STORAGE AND DISPOSAL:

Store in a corrosive resistant container with a resistant inner liner.

Store locked up.

Dispose of contents/container in accordance with local regulations.

**24 Hour Emergency
Transportation Number:
1-800-255-3924**



567-QA100

NET CONTENTS: 55 GAL (555 LBS)

Modern Solutions by:

ENVIROTECH

CHEMICAL SERVICES, INC.

MODESTO, CA 95358

www.envirotech.com