

### APPLICATIONS

**Perasan® MP-2C** is a food grade sanitizer for use on meat, poultry, and seafood in accordance with FCN #699, #887, #908, #887, #1132, #1419, #1738, and #1806 and is listed on FSIS Directive List 7120.1. **Perasan® MP-2C** is also approved for On-line and Off-line Reprocessing as listed in the 7120.1 List. **Perasan® MP-2C** can also be applied in process water or directly on further processed fruits and vegetables in accordance with FCN #1738. Enviro Tech's peracetic acid products are designed to decrease the incidence of pathogenic organisms in or on food and help reduce the number of decay or food spoilage organisms. This product is only available through select, premium distributors.

### PROPERTIES

**Perasan® MP-2C** has a high oxidation potential and is very reactive. It exhibits excellent bactericidal and fungicidal activity against a wide range of microorganisms in cold or warm water. Product is stable for a minimum of 9-12 months under normal conditions if kept out of sunlight. **Perasan® MP-2C** is significantly more concentrated than comparable 15% PAA products. **Perasan® MP-2C** has one of the lowest hydrogen peroxide to PAA ratios of on the market, which reduces the potential of bleaching carcasses and darkening of wingtips in poultry processing.

### CHEMICAL COMPOSITION

**Perasan® MP-2C** is an equilibrium mixture of peracetic acid, hydrogen peroxide, acetic acid, and water. 1 oz. of this product in 10 gallons of water yields 190 ppm as PAA, whereas a comparable 15% product yields a 129 ppm residual (a 46% difference).

Peracetic acid (% wt)	21.8-22.8
H <sub>2</sub> O <sub>2</sub> (% wt)	4.7-5.2
Acetic acid (% wt)	40-50

### PHYSICAL PROPERTIES

Density 20°C (68°F), (g/ml)	1.11 (9.28#/gal)
Vapor Pressure 25°C (78°F), (mmHg)	46.8
pH (190 ppm as PAA, in tap water), 20°C (68 °F)	4.0-5.5
Flash Point (DIN 51584)	>93° C (>200° F)
Freezing Point	< -8° C (17° F)

### APPEARANCE

Clear, colorless liquid (pungent vinegar-like odor).

### AUTHENTICATION

Evidenced by the food safety and security holographic sticker on the label.

### STORAGE

The **Perasan® MP-2C** container must be stored in an upright position. The storage area should be well ventilated, ≤86°F, and shaded from sunlight as well as protected from sources of radiant heat. Contamination of the product, especially with non-stainless steel metal ions and alkali must be avoided.

### SHELF LIFE

At least 9-12 months without notable loss of active oxygen if stored properly.

### PACKAGING

5 gal (40 lb), 53 gal (490 lb), and 300 gal (2780 lb).

### TRANSPORT (DOT)

UN3109, Organic peroxide type F, liquid (≤25% peracetic acid with ≤26% hydrogen peroxide), 5.2 (8)

Prod. #844 (V-1/7/2019)

All information and statements contained herein are believed to be accurate at the time of publication, but Enviro Tech Chemical Services, Inc. makes no warranty with respect thereto, including but not limited to any results to be obtained or the infringement of any proprietary rights. Use or application of such information or statements is at user's sole discretion, without any liability on the part of Enviro Tech. Nothing herein shall be construed as a license of or recommendation for use which infringes upon any proprietary rights. Use of this product shall be the sole responsibility of user, and Enviro Tech shall not be liable in any way for said use, other than reimbursement for the actual cost of product.