

## **PERAFOAM™**

# TECHNICAL DATA

### **APPLICATIONS**

**Perafoam™** is a very high foaming concentrate specially designed for use in conjunction with Enviro Tech's peroxyacetic acid sanitizer/disinfectant products, such as **Perasan® A**. It is liquid and is easily dispensed at temperatures as low as 35 °F (2 °C). **Perafoam™** is hard water tolerant and stable to oxidizers. Its long-lasting foam and surfactant package allows for longer contact on equipment and vertical surfaces than conventional methods. This results in superior sanitation and greater efficacy of peroxyacetic acid products.

### **PROPERTIES**

**Perafoam™** uses only FDA-approved GRAS status ingredients and can be utilized in federally inspected meat, poultry, and seafood plants. No rinse is required if used at the recommended dose rates.

### PHYSICAL PROPERTIES

Color	Colorless, clear
Scent	Mild soap odor
Specific gravity (at 20 °C)	1.05
Refractive Index (% Brix)	18.00-20.00
Density (lbs/gal.)	8.76
pH (1%)	7.0-8.0
Viscosity (at 20 °C)	35-55 cSt

### **DIRECTIONS FOR USE**

### For Use With Perasan® A as a Cleaner:

Manually or mechanically blend 6 fl. oz. of this product to 6 gal of water. The dilution water may be ambient up to 150° F. For food contact surfaces, add 1.0–2.4 fl. oz. of **Perasan® A**. Add this blend through a conventional foam generating device (foamer) and adjust settings to obtain the desired foam characteristics. It is preferable to leave the foam product on equipment as long as possible before rinsing, but a potable rinse is not required. If used for Organic Production, a sanitizing rinse is required

### **General Foam Additive Uses:**

Manually or mechanically blend 4-24 fl. oz. of this product to 6 gal of water (0.6-4 fl oz per gal) and then add the 2nd product of choice to the solution and mix thoroughly. Apply through a conventional foam generating device and adjust foam to desired characteristics.

#### **IMPORTANT**

Read and understand label and Safety Data Sheet (SDS) for complete listing of hazards, precautions, first aid statements, and storage and handling information. SDS Sheets are available from the distributor of this product. 24-Hour Emergency Response Line 1-800-255-3924.

Toll Free: (888) 563-2254

Fax: (209) 581-9653

Prod. #98 (V-1/7/2019)

All information and statements contained herein are believed to be accurate at the time of publication, but Enviro Tech Chemical Services, Inc. makes no warranty with respect thereto, including but not limited to any results to be obtained or the infringement of any proprietary rights. Use or application of such information or statements is at user's sole discretion, without any liability on the part of Enviro Tech. Nothing herein shall be construed as a license of or recommendation for use which infringes upon any proprietary rights. Use of this product shall be the sole responsibility of user, and Enviro Tech shall not be liable in any way for said use, other than reimbursement for the actual cost of product.